

**2088 Series Diaphragm Pump  
Premium Demand Pump w/Fin  
Cooled Motor  
(12 VDC)**



Premium Pump w/ cooling fins      Standard

Model	2088-514-145			
Description	3.6 GPM open flow, Santoprene <sup>®</sup> valves, Santoprene <sup>®</sup> diaphragm, 45 PSI Demand Switch, 1/2" MSPT ports (1/2" - 14 National American Straight Pipe Thread, requires SHURflo swivel type fittings), Poly Housing			
Voltage	12 VDC			
PSI	10	20	30	40
BAR	0.7	1.4	2.1	2.8
GPM	2.90	2.60	2.30	2.07
L/min	11.0	9.8	8.7	7.8
Amps	5.6	7.1	8.4	9.0

\* Additional technical information is available below in PDF format.  
Adobe Acrobat Reader is required to view these documents.

[Troubleshooting](#) | [Replacement Parts](#)

close window ▶



SHURflo Pump Manufacturing Company  
5900 Katella Ave  
Cypress, Ca 90630  
Phone: 562-795-5200 or 800-854-3218  
Fax: 562-795-7564  
E-mail: [customer\\_service@shurflo.com](mailto:customer_service@shurflo.com) or [literature@shurflo.com](mailto:literature@shurflo.com)

